




Lockable Flexible Conduits

These Corrugated Conduits are made from modified Polypropylene. They are very flexible, acid-proof, flame-retardant and have high cold impact strength. It is used in engine compartment, car body interior, machining industry, home appliance industry, heating and air-conditioning installations, ship and train building. Mounting tools are available for opening and closing of these conduits.

Technical Data

Material	Modified Polypropylene
Colour	RAL 9005 (Black)
Temperature Range	-40° C to +135° C Continuous, +150° C Intermittent

Accessories

Image	Cat. no.	Description
	Mounting Clips	Mounting Clips are used for supporting conduits. These clips are...

Ordering Information

Cat. No.	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius R (mm)	Standard Pack (meters)
SPPM-8.5	8.6	13.3	47	50
SPPM-10L	10.2	13.2	47	50
SPPM-11	11.2	16.3	50	50
SPPM-13	12.2	18.9	50	50
SPPM-15	14.9	22	55	50
SPPM-19	19	26.2	65	50
SPPM-26	24.6	32	70	25

Opening Tool For SPPM1 - 8.5

Opening Tool Cat. No.	Standard Pack for Tool (pieces)
SPPM1 - 8.5	1

Opening Tool For SPPM1 - 11

Opening Tool Cat. No.	Standard Pack for Tool (pieces)
SPPM1 - 11	1

Opening Tool For SPPM1 - 13

Opening Tool Cat. No.	Standard Pack for Tool (pieces)
SPPM1 - 13	1

Opening Tool For SPPM1 - 50

Opening Tool Cat. No.	Standard Pack for Tool (pieces)
SPPM1 - 50	1