



Lockable Flexible Conduits

These Corrugated Conduits are made from modified Polypropylene. They are very flexible, acid-proof, flame-retardant and have high cold impact strength. It is used in engine compartment, car body interior, machining industry, home appliance industry, heating and air-conditioning installations, ship and train building. Mounting tools are available for opening and closing of these conduits.

Technical Data

| | |
|-------------------|--|
| Material | Modified Polypropylene |
| Colour | RAL 9005 (Black) |
| Temperature Range | -40° C to +135° C Continuous, +150° C Intermittent |

Accessories

| Image | Cat. no. | Description |
|-------|----------------|---|
| | Mounting Clips | Mounting Clips are used for supporting conduits. These clips are... |

Ordering Information

| Cat. No. | Inner Diameter (mm) | Outer Diameter (mm) | Bending Radius R (mm) | Standard Pack (meters) |
|----------|---------------------|---------------------|-----------------------|------------------------|
| SPPM-8.5 | 8.6 | 13.3 | 47 | 50 |
| SPPM-10L | 10.2 | 13.2 | 47 | 50 |
| SPPM-11 | 11.2 | 16.3 | 50 | 50 |
| SPPM-13 | 12.2 | 18.9 | 50 | 50 |
| SPPM-15 | 14.9 | 22 | 55 | 50 |
| SPPM-19 | 19 | 26.2 | 65 | 50 |
| SPPM-26 | 24.6 | 32 | 70 | 25 |

Opening Tool For SPPM1 - 8.5

| Opening Tool Cat. No. | Standard Pack for Tool (pieces) |
|-----------------------|---------------------------------|
| SPPM1 - 8.5 | 1 |

Opening Tool For SPPM1 - 11

| Opening Tool Cat. No. | Standard Pack for Tool (pieces) |
|-----------------------|---------------------------------|
| SPPM1 - 11 | 1 |

Opening Tool For SPPM1 - 13

| Opening Tool Cat. No. | Standard Pack for Tool (pieces) |
|-----------------------|---------------------------------|
| SPPM1 - 13 | 1 |

Opening Tool For SPPM1 - 50

| Opening Tool Cat. No. | Standard Pack for Tool (pieces) |
|-----------------------|---------------------------------|
| SPPM1 - 50 | 1 |