



Plastic Sealite Conduit With Smooth Cover - ANMSF

These all-plastic sealite conduits provide good mechanical protection of cables in less demanding applications such as the general machine and apparatus building industries. When used in combination with a polyamide fitting an IP 67 leak-tight cable protection system with strong pull-out strength is achieved.

Technical Data

Colour		Grey
Temperature Range		-20° C to +80° C Continuous, Intermittent upto +100° C
Protection Class		IP 67 (dust proof, water tight)
Tensile Strength		Class 4, Heavy (1000 N)
Compression Ressitance		Class 1, Very Light (125 N)
Impact Resistance		Class 3, Medium (2 J)

Accessories

Image	Cat. no.	Description
	P Type Mounting Clips	'P' type mounting clips are ideal elements for retaining /...

Approvals



Product Drawing



Ordering Information

Cat. No.	Inner Diameter (mm)	Outer Diameter (mm)	Size	Bending Radius Static R (mm)	Bending Radius Dynamic R (mm)	Standard Pack (meters)
ANMSF-3/8"	12.6	17.8	3/8"	70	100	30
ANMSF-1/2"	16	21.1	1/2"	100	135	30
ANMSF-3/4"	21.1	26.4	3/4"	130	175	30
ANMSF-1"	26.8	33.1	1"	180	220	30
ANMSF-1 1/4"	35.4	41.8	1 1/4"	225	270	15
ANMSF-1 1/2"	40.3	47.8	1 1/2"	255	320	15
ANMSF-2"	51.6	59.9	2"	310	400	15