




Stainless Steel Square Locked Conduits - Type ASLI

These conduits provide high mechanical and chemical protection in applications that require a high degree of corrosion protection. Typical applications include the steel, foundry, marine and shipbuilding industries as well as machine building.

Technical Data

Colour	Metal
Temperature Range	-100° C to +600° C
Protection Class	IP 40
Tensile Strength	Heavy (1000 N)
Compression Ressitance	Heavy (1250 N)
Construction	Square-Locked Core Stainless Steel (AISI-304), Also available in (AISI-316)
Impact Resistance	Heavy (6 J)

Accessories

Image	Cat. no.	Description
	P Type Mounting Clips	'P' type mounting clips are ideal elements for retaining /...

Approvals



Product Drawing



Ordering Information

Cat. No.	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius R (mm)	Size	Standard Pack (meters)
ASLI-3/16"	4.8	6.9	23	3/16"	30
ASLI-5/16"	10.1	12.8	50	5/16"	30
ASLI-3/8"	12.6	15.5	60	3/8"	30
ASLI-1/2"	16	18.9	75	1/2"	30
ASLI-3/4"	21	23.9	90	3/4"	30
ASLI-1"	26.5	30	120	1"	30
ASLI-1 1/4"	35.1	38.7	135	1 1/4"	30
AUI-1 1/2"	40.3	44.4	230	1 1/2"	15
AUI-2"	51.6	55.7	285	2"	15